


PureWaterCooler™

by VERTEX



Lo-Profile Countertop Water Cooler

Hot and cold bottle-less cooler with built in filtration makes clean great tasting water. Sleek compact design fits under standard cabinets.

Two Temperatures

- Hot and Cold

Standard Features

- Built-In Reverse Osmosis or standard filtration system.
- Single dispensing faucet with HOT and COLD button control.
- Dual button safety feature for HOT.
- Low Height (only 16 1/2") fits under standard cabinets.
- Solenoid valve inlet water control.
- Indicator lights on front panel for heating and cooling.
- On/off switch in rear to control hot and cold functions.

Special Features

- Built-In Moisture Sensor shuts off water if leak occurs.
- Cold 37 - 50°F, adjustable.
- Hot 180°F, auto control.
- High efficiency sealed compressor.



Side panel removes for easy access to filters

Specifications

Shipping Weight: 50 lb.
 Dimension: 13"W x 14"D x 16.5"H
 Cold tank volume 0.75 gal
 Hot tank volume 1.0 qt.
 Cooling Rate: 1.5 gal/hr 37-50 °F
 Heating Rate: 1.5 gal/hr 180 °F
 Voltage: 115 VAC
 Power Required: 600w max

Conforms to UL Std. 399



Filter System

Standard Filter **400F**
Stage 1: 5 micron Sediment
Stage 2: 10 micron Activated Carbon
 Reverse Osmosis Filter **400R**
 Above 2 stages plus
Stage 3: 50-GPD RO Membrane
 Automatic tank full control
 Fully assembled
 - connection hardware included

ORDERING INFORMATION

2-Temp Dispenser - 50 GPD Reverse Osmosis	PWC-400R
2-Temp Dispenser - Standard Filtration	PWC-400F
With UV stage option	add /UV
Replacement Filters	
Sediment	IFA-4035
GAC Carbon	IFA-4034
RO membrane, 50 GPD	MA-4203